

## SS-651 Marking Unit

### Standard Etching Unit for Low to Medium Volume

This power unit is simple and economical. It includes medium power transformer, variable intensity control dial, and AC mark DC etch. The unit supplies constant power to the marking head at all times. The output in the 651 Series is maintained by the linear rheostat control allowing a variable output level of 0-10 amps, AC or DC.



- SS-651 Power Unit
- 4650 Carbon Marking Cartridge
- 4397 (1 1/2" x 1/2") Hand Marker with 4397-1 Marking Screens
- 9012-BL Stencil Paper (100pc./bx)
- Electrolyte Tray (p/n 1025)
- 4309-BA Standard Cord Set
- 3121-3D Deep Etch Pads (10/pk)
- SC-44 Electrolyte and Neutralyte
- 9007-BCF Stencil Paper (50' roll)
- Wiping Tissues (p/n 2500)
- Marking Manual

Custom items may be substituted or added to any order

#### Catalog

- [Marking Devices](#)
  - [SS-651](#)
  - [SS-751](#)
  - [SS-851](#)
  - [SS-211](#)
  - [GA-961-1 & GA-961-2](#)
  - [SSA-1001](#)
- [Hand Marker & Accessories](#)
- [Bench Marker & Accessories](#)
- [Stencils](#)
- [Electrolytes & Cleaners](#)
- [Request a Catalog](#)

**ELECTROLYTE  
TABLE**

[View Table >](#)

**REQUEST  
INFORMATION**

[Get Info >](#)

**STATE  
OF  
THE  
MARK.**

Questions or to place an order, call us at 1.800.775.3824 or email at [info@img-electromark.com](mailto:info@img-electromark.com)